

CERTIFICATE OF COMPLIANCE

Certificate Number 20190807-E210608
Report Reference E210608-20120614
Issue Date 2019-AUGUST-07

Issued to: Turck Inc.
3000 Campus Drive, Minneapolis MN 55441-2619

This certificate confirms that PROXIMITY SWITCHES
representative samples of See Addendum Page.


Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 508 & CSA 22.2 No. 14-18, Industrial Control Equipment
Additional Information: See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20190807-E210608
Report Reference E210608-20120614
Issue Date 2019-AUGUST-07

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Inductive Linear Position Sensors/Switches Cat. No. LIXXXPX-QXXLMX, where X is a numerical character, may be followed by E, followed by multiple alpha-numeric characters, may be followed by /S or /CS and a 2 to 5 digit number, may be followed by / followed by 3, followed by G or D or GD.

Inductive Angular Position Sensors/Switches Cat. No. RIXXXPX- may be followed by E, followed by QRXX, may be followed by MX, where X is a numerical character, may be followed by blank or H11, may be followed by two digits, may be followed by fifteen digits, may be followed by /S or /CS and a 2 to 5 digit number, may be followed by / followed by 3, followed by G or D or GD.

Inductive Angular Position Sensors/Switches Cat. No. RIXXXPX-DSU35, where X is a numerical character, may be followed by multiple alpha-numeric characters, may be followed by /S or /CS and a 2 to 5 digit number, may be followed by / followed by 3, followed by G or D or GD.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

